

## Epifanes Nonskid Deckcoating (all colours)

### Hard nonskid deck paint

<b>Type</b>	Air drying
<b>Base</b>	Urethane/alkyd resin / polypropylene beads
<b>Properties</b>	A one-component, semi-gloss, nonskid deckpaint containing measured amount of polypropylene beads as the nonskid agent.
<b>Field of application</b>	Fiberglass/GRP - Steel - Wood - aluminum: as nonskid finishing deckcoating on full one-component paint systems. Maintenance of existing nonskid paint systems regardless which brand.
<b>Colours</b>	White - cream # 1 - grey # 212 - grey # 213 Custom made colours on request
<b>Gloss</b>	Semi gloss
<b>Density</b>	1,30 - 1,50 kg/dm <sup>3</sup> dependent on colour
<b>Viscosity</b>	35 seconds ISO-cup 6 mm
<b>Solids contents</b>	50-55 +/- 2 vol. %
<b>VOC - level</b>	367 grams/liter
<b>Packing</b>	750ml. Grey # 212 and grey # 213 also available in 2000ml.
<b>Shelf life</b>	In closed original container stored in a dark location between 5 - 25°C approx. 3 years.
<b>Conditions during application and drying</b>	Temperature                      minimal 10°C. - maximum 28°C. Relative air humidity           minimal 50% - maximum 75%
<b>Thinner for roller applications</b>	Epifanes Brushthinner for Paint & Varnish
<b>Thinner for spray applications</b>	Application by spray is not advised
<b>Application tools</b>	Shorthaired fur roller
<b>Recommended filmthickness / coat</b>	100 - 120 µm wet = 50 - 60 µm dry
<b>Application recommendations</b>	Stir well prior to use and during application. Apply in one single rolling movement. Do not apply wet-in-wet. Do not apply excessive wet films to avoid the formation of curtains and drying problems. Application by short-haired fur roller provides an even distribution of the beads. For best results, apply 2 coats. Allow the final coat at least 72 hours to harden thoroughly.
<b>Theoretical coverage</b>	4- 8m <sup>2</sup> per liter @ 50µm dry filmthickness
<b>Practicle coverage</b>	Dependent on condition of substrate, loss of material due to factors such as application technique, shape of object, circumstances during application.
<b>Substrate conditions</b>	To avoid the intake of moisture, apply this Nonskid Deckcoating on at least 2 high gloss coats.

# Epifanes Nonskid Deckcoating (all colours)

## Hard nonskid deck paint

**Drying times @ 20°C. / 65% RAH  
and 40 µm dry filmthickness**

Dustdry	Recoatable	Min. through drying
1 hour	24 hours	72 hours

**Preferred primer build up  
(one-component)**

GRP	Steel	Wood	Aluminium
Epifanes Multi Marine Primer	Epifanes Multi Marine Primer	Epifanes Multi Marine Primer	Epifanes Multi Marine Primer
1 coat	3 coats	1-2 coats	1-2 coats
+	+	+	+
Epifanes Mono-urethane Yacht Paint	Epifanes Mono-urethane Yacht Paint	Epifanes Mono-urethane Yacht Paint	Epifanes Mono-urethane Yacht Paint
2 coats	2 coats	2 coats	2 coats

**Remark regarding primer system**

Sand every primer coat with P 220 dry. On **new** aluminium, first apply one thin coat Epifanes Washprimer AQ.

**System build up**

For optimal distribution of the nonskid beads, apply two coats Nonskid Deckcoating. Intercoat sanding is not necessary.

**Safety**

The user of this product should obey all national laws and legislation concerning health, safety and environmental hazard. For more information on health and safety, refer to the Material Safety Data Sheet of this product.

Although the facts and suggestions in this product information sheet are based on our own research and field experiences and are believed reliable, we cannot simply be held responsible for performance or results obtained through the use of this product. Ineffectiveness or other unintended consequences may result, because of such factors as weather, conditions, presence or other materials or the manner of preparation, use or application all of which are beyond W. Heeren & Zoon's control. All such risks are assumed by user.

**DISCLAIMER OF WARRANTIES.** Seller makes no express warranties.

THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE EXCLUDED. In the event a warranty is created by law, buyer's EXCLUSIVE REMEDY shall be the replacement of any defective product. No other remedy ( including, but not limited to, incidental or consequential damages for lost profits, lost sales, injury to person or property, or any other incidental or consequential loss ) shall be available to buyer.

November 2012